

LIMEPAINT

NATURA (ref. MP100-8KG)



STOOPEN & meeûs

SINCE
1894

DESCRIPTION :

Lime paint(mineral paint, dry paint) for application in and outside.

This paint looks like chalk wit minerals and is extremely suitable for different decorative painting techniques and renovation of old buildings.

Most important characteristics: mat, mineral paint (high decorative value), different finish possible. Dry paint (mix with water for application)

High water permeability. Good endurance outside. Water based paint. Ecologically sound.

PACKING :

This lime paint is delivered in buckets of 8 kg, "base" dry powder.

The pigments are sold separately in order to let anyone choose his personal tint and intensity by adding a certain amount of dry pigment.

Pigments are offered in boxes of 0,4 kg (1 bucket of 8kg paint in powder needs 5% pigment) 2 to 3 boxes can be added to 8kg basic product to obtain deep, intense colours.

Different pigments can be mixed without any problem.

TECHNICAL CHARECTERISTICS :

Form : white powder

Density : 0,6 kg/l powder lime paint - 1,30 kg/ l liquid lime paint

pH : 11 à 12

Quantity of water : 1,0 - 1,2 l/kg depending of the foundation, paint technique and the pigmentation

Number of layers : 1-2 depending the foundation en the required view - 1 layer is already covering

Consumption : 1-2 kg dry powder / 10 m²/layer, strongly depending on the foundation, thickness off the layer and the used technique

Sticking : very good weather fastness - powder can be released under the influence of acid rain or immediacy of the sea

Period to dry : 1-5 hours: depending of the circumstances - protect against moisture during 72 hours

Period to harden : fully hardened after 2-3 months by carbonisation (result: 2-3 x stronger)

Temperature : ambient temperature and the temperature of the foundation should be between 8° and 30°, min 8° during 48 hours
avoid wind, direct sunlight and rain

Durability : min; 1year : in dry and closed packing - min 1 month mixed with water in closed packing

Tools : apply with a big paint brush, inox knife our role brush

Cleaning tools : water

FOUNDATION :

OUTSIDE :

Mineral, absorbing foundation, clean and fat-free

Loose parts have to be removed, loose joints have to be repaired before painting

The foundation has to be wetted first in case of strongly absorbing foundations and surely with high temperatures or strong wind

Sufficient wetting of the foundation will positively influence the handling and drying

When the foundation is to dry or when the layers are very thick, shrink ruptures may occur

You can repair the ruptures wit an thin extra layer.

INSIDE :

All mineral foundations but also old layers of paint, wood, MDF, metal etc. if the foundation is sufficiently stable

You can work with a water based primer If the foundation has different degrees of absorption to avoid spots

PREPARATION :

The powder is packed in a plastic bag , the pigments are packed in units of 400 gr

Remove the plastic bag from the bucket, pour +/- 8l water in the bucket (till the mark) add the full quantity of pigment, mix strongly

Then add the powder gradually and mix all. Lime paint has to be mechanically mixed 3 till 5 minutes to obtain a smooth, homogeneous substance

Make sure to make sufficient paint to paint at least one layer on the entire wall

If necessary stir or add a little water and mix again but beware of differences in colour by diluting or extra mixing

PRECAUTIONS :

The product is strongly alkali: protect eyes and skin to prevent irritation

In case of contact with the eyes: rinse thoroughly with lots of water. In case of prolonging irritation: consult a physician

Always mix the chalk in open air or in well ventilated places

R 36/38 irritant to eyes and skin

R 37 Irritating to bronchial tubes

R 41 danger for serious eye damage

R 43 Sensitive to skin

S 2 keep away from children

S 22 Do not inhale dust

S 24/25 avoid contact with skin and eyes


S 27 Remove immediately contaminated clothes

S 26 after contact with eyes: rinse thoroughly with lots of water. seek medical advice

S 28 after contact with skin: rinse thoroughly with water and soap

S 36/37/39 wear suitable protective clothing, gloves and goggles

S 38 wear protective mask if ventilation is insufficient



Xi : irritant

Remark

We guarantee the same quality of our products but we can never accept liability regarding the processing of our products

Anc. Ets. Stoopen & Meeûs

Van Praetstraat, 22

B-2660 Hoboken

Tel. 03/825 00 55

Site : www.stoopen-meeus.com

Email : dragon@stoopen-meeus.com

Revision date : 27/11/2007